

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 17361
Issue date: 07.10.2021 Revision date: 16.12.2022 Supersedes version of: 11.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : 045894 TRAFIC PAINT - BLUE 20KG
UFI : WPKE-TOHT-E306-EFQG
Product code : 045894

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use
Use of the substance/mixture : PAINT

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Supplier**

BLINKER ESPAÑA, S.A.U.
Pol. Ind. Las Atalayas, parcelas 11, 12 y 13
03114 Alicante
Spain
T +34 966 10 25 00 - F +34 966 10 25 01
msds@blinkergroup.com - www.blinkergroup.com

Distributor

BLINKER FRANCE, S.A.R.L.
Allée de Barcelone, Les Bureaux du Parc Bât. B
66350 Toulouges
France
T +33 468 68 09 74 - F +33 468 55 31 99
blinkerfrance@blinkerfrance.com - www.blinkergroup.com

Distributor

BLINKER PORTUGAL, LDA.
Parque Oriente, R.D. Nuno Alvares Pereira, nº4 bl. 1 r/c
2695-167 Bobadela
Portugal
T 21 9112530 - F 21 9112539
blinker@blinker.pt - www.blinkergroup.com

1.4. Emergency telephone number

Emergency number : ESPAÑA: 954 37 12 33 (INTCF) // PORTUGAL: 800 250 250 (CIAV) // FRANCE: 05 61 77 74 47

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226
Acute toxicity (inhalation:dust,mist) Not classified
Skin corrosion/irritation, Category 2 H315
Skin sensitisation Not classified
Specific target organ toxicity (single exposure) Not classified
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

045894 TRAFIC PAINT - BLUE 20KG


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Hazard statements (CLP)

Precautionary statements (CLP)

Extra phrases

- : Warning
- : H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
- : P210 - Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P262 - Do not get in eyes, on skin, or on clothing.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331 - Do NOT induce vomiting.
P370+P378 - In case of fire: Use media other than water for extinction.
- : EUH208: .
Fatty acids, C18, unsatd, dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine.
May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	10 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Reaction mass of ethylbenzene and xylene	REACH-no: 01-2119486136-34	10 – 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
1-methoxy-2-propanol; monopropylene glycol methyl ether	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435-35	0 – 20	Flam. Liq. 3, H226 STOT SE 3, H336

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	1 – 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
2,6-dimethylheptan-4-one	CAS-No.: 108-83-8 EC-No.: 203-620-1 EC Index-No.: 606-005-00-X REACH-no: 01-2119474441-41	0 – 10	Flam. Liq. 3, H226 STOT SE 3, H335
Titanium dioxide	CAS-No.: 13463-67-7 EC-No.: 236-675-5 REACH-no: 01-21119489379-17	2,5 – 10	Not classified
Methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	0 – 3	Flam. Liq. 2, H225 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Oral), H301 STOT SE 1, H370
2-methoxy-1-methylethyl acetate	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	0 – 2,5	Flam. Liq. 3, H226
Carbon black	CAS-No.: 1333-86-4 EC-No.: 215-609-9 REACH-no: 01-2119489801-30	0 – 2,5	Not classified
Quartz (breathable fraction)	CAS-No.: 14808-60-7 EC-No.: 238-878-4	0 – 1	STOT RE 1, H372
Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine	CAS-No.: 162627-17-0 REACH-no: 01-2119970640-38	0,1 – 1	Skin Sens. 1A, H317
n-butyl acrylate	CAS-No.: 141-32-2 EC-No.: 205-480-7 EC Index-No.: 607-062-00-3 REACH-no: 01-2119453155-43	0 – 1	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
2-methoxypropyl acetate	CAS-No.: 70657-70-4 EC-No.: 274-724-2 EC Index-No.: 607-251-00-0	0 – 0,3	Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H335
Maleic anhydride	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9 REACH-no: 01-2119472428-31	0 – 0,001	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372

Full text of H- and EUH-statements: see section 16

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of water/... Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Causes skin irritation.
-------------------------------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools.
Hygiene measures	: Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA	221 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Portugal - Occupational Exposure Limits	
Local name	Xileno (isómeros)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Spain - Occupational Exposure Limits	
Local name	Xilenos, mezcla isómeros
VLA-ED (OEL TWA) [1]	221 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	442 mg/m ³
VLA-EC (OEL STEL) [ppm]	100 ppm

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Xylene (1330-20-7)	
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
United Kingdom - Occupational Exposure Limits	
Local name	Xylene, o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [1]	220 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	441 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Face shield. Category II. Wear security glasses which protect from splashes. Eye protection. EN 165. ISO 16321-1. EN 167. EN 168. Face shields must have a field of vision with a centerline dimension of at least 150mm vertically when fitted to the frame.

8.2.2.2. Skin protection

Skin and body protection:

Antistatic clothing. Category II. EN 340. EN 1149-1. EN 1149-2. EN 1149-3. EN 1149-5

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

If the product is used correctly, no individual protection equipment is necessary.

Other skin protection

Materials for protective clothing:

Safety foot-wear. antistatic boots. Category II. EN ISO 13287. EN ISO 20344. EN ISO 20346

8.2.2.3. Respiratory protection

Respiratory protection:

If the recommended technical measures are followed, no individual protection equipment is necessary.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 33 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1,516
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 31,949 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified.

045894 TRAFIC PAINT - BLUE 20KG

ATE CLP (dermal)	3356 mg/kg
------------------	------------

Xylene (1330-20-7)

LD50 oral rat	2100 mg/kg
---------------	------------

LD50 dermal rat	1100 mg/kg
-----------------	------------

LC50 Inhalation - Rat	11 mg/l/4h
-----------------------	------------

ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg
---------------	------------

LD50 dermal rabbit	15354 mg/kg
--------------------	-------------

LC50 Inhalation - Rat	17,2 mg/l/4h
-----------------------	--------------

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LD50 oral rat	> 3000 mg/kg
---------------	--------------

LD50 dermal rat	2000 mg/kg
-----------------	------------

LC50 Inhalation - Rat	54,6 mg/l/4h
-----------------------	--------------

Methanol (67-56-1)

LD50 oral rat	1978 mg/kg
---------------	------------

LD50 dermal rabbit	15800 mg/kg
--------------------	-------------

LC50 Inhalation - Rat	83,9 mg/l/4h
-----------------------	--------------

2,6-dimethylheptan-4-one (108-83-8)

LD50 oral	> 2000 mg/kg
-----------	--------------

Maleic anhydride (108-31-6)

LD50 oral rat	400 mg/kg
---------------	-----------

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Maleic anhydride (108-31-6)	
LD50 dermal rat	610 mg/kg
LC50 Inhalation - Rat	4,35 mg/l (1 h)
Reaction mass of ethylbenzene and xylene	
LD50 oral rat	3761,5 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 Inhalation - Rat [ppm]	6525 ppm/4h
Titanium dioxide (13463-67-7)	
LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 5,09 mg/l/4h
2-methoxy-1-methylethyl acetate (108-65-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	30 mg/l/4h
n-butyl acrylate (141-32-2)	
LD50 oral rat	900 mg/kg
LD50 dermal rabbit	750 mg/kg
LC50 Inhalation - Rat	10,3 mg/l/4h
Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LD50 dermal rabbit	> 3000 mg/kg
LC50 Inhalation - Rat	> 27 mg/l (1 h)
2-methoxypropyl acetate (70657-70-4)	
LD50 oral rat	400 mg/kg
LD50 dermal rat	610 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified.
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified.
Additional information	: Based on available data, the classification criteria are not met
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2,6-dimethylheptan-4-one (108-83-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

n-butyl acrylate (141-32-2)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

2-methoxypropyl acetate (70657-70-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified
Additional information : Based on available data, the classification criteria are not met

ethylbenzene (100-41-4)

STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
------------------------	---

Quartz (breathable fraction) (14808-60-7)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Maleic anhydride (108-31-6)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : Not classified
Additional information : Based on available data, the classification criteria are not met

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

12.2. Persistence and degradability

045894 TRAFIC PAINT - BLUE 20KG

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

045894 TRAFIC PAINT - BLUE 20KG

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 1263

UN-No. (IMDG) : UN 1263

UN-No. (IATA) : UN 1263

UN-No. (ADN) : UN 1263

UN-No. (RID) : UN 1263

14.2. UN proper shipping name

Proper Shipping Name (ADR) : PAINT

Proper Shipping Name (IMDG) : PAINT

Proper Shipping Name (IATA) : Paint

Proper Shipping Name (ADN) : PAINT

Proper Shipping Name (RID) : PAINT

Transport document description (ADR) : UN 1263 PAINT, 3, III, (D/E)

Transport document description (IMDG) : UN 1263 PAINT, 3, III

Transport document description (IATA) : UN 1263 Paint, 3, III

Transport document description (ADN) : UN 1263 PAINT, 3, III

Transport document description (RID) : UN 1263 PAINT, 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3



045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III
Packing group (RID) : III


14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 367, 650
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Transport category (RID) : 3
Colis express (express parcels) (RID) : CE4
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 31,949 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Quartz (breathable fraction),2-methoxypropyl acetate are listed

SZW-lijst van mutagene stoffen : 2-methoxypropyl acetate is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : Xylene,2-methoxypropyl acetate are listed

Denmark

Class for fire hazard : Class II-1

Store unit : 5 liter

Classification remarks : R10 <H226;H315>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.

045894 TRAFIC PAINT - BLUE 20KG

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
Repr. 1B	Reproductive toxicity, Category 1B
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.